

SUCTION LINE FILTER DSF SERIES


IMAGE, DRAWINGS & MODEL AVAILABLE




DIMENSIONAL DATA




PLEATED
FILTER
INSIDE




DRAWING -1



DRAWING -2





DRAWING -3



DRAWING -4

SR NO.	MODEL	CONNECTION TYPE (inch)	OUTER DIA ØA		BODY LENGTH B		STOPPER TO STOPPER LENGTH C		OVERALL LENGTH D		REFER DRAWING NO.
			mm	inch	mm	inch	mm	inch	mm	inch	
1	DSF-163S	3/8"ODF	63.5	2.5	110	4.34	136.3	5.37	160	6.3	DRAWING -2
2	DSF-164S	1/2" ODF	63.5	2.5	110	4.34	136.3	5.37	160	6.3	DRAWING -2
3	DSF-165S	5/8" ODF	63.5	2.5	110	4.34	136.3	5.37	160	6.3	DRAWING -2
4	DSF-165ORN	5/8" O RING	63.5	2.5	110	4.34	136.3	5.37	170	6.7	DRAWING -1
5	DSF-166ORN	3/4" O RING	63.5	2.5	110	4.34	136.3	5.37	203	8	DRAWING -3
6	DSF-415S	5/8" ODF	88.9	3.5	159	6.25	189	7.44	209	8.2	DRAWING -2
7	DSF-416S	3/8"ODF	88.9	3.5	159	6.25	189	7.44	209	8.2	DRAWING -2
8	DSF-417S	7/8"ODF	88.9	3.5	159	6.25	189	7.44	233	9.2	DRAWING -4
9	DSF-419S	1"-1/8 ODF	88.9	3.5	159	6.25	189	7.44	243	9.6	DRAWING -4

DIMENSIONAL DATA



SR NO.	MODEL	CONNECTION TYPE (inch)	OUTER DIA ØA		BODY LENGTH B		STOPPER TO STOPPER LENGTH C		OVERALL LENGTH D		REFER DRAWING NO.
			mm	inch	mm	inch	mm	inch	mm	inch	
1	DSF-7511s	1-3/8" ODF	88.9	3.5	208	8.19	263	10.35	313	12.32	DRAWING
2	DSF-7513S	1-5/8" ODF	88.9	3.5	208	8.19	263	10.35	313	12.32	

- INTERNAL ASSEMBLY - FILTER
- MAXIMUM WORKING PRESSURE - 35 bar (508 psig)
- 'O'RING TYPE CONNECTION ARE IN STEEL,NICKEL PLATED
- ODF TYPE CONNECTION IS IN COPPER
- * MARK CONNECTION STEEL, PLATED

Connection Type (Solder) ←
 Connection Size (5/8") ←
 Cubic Inch ←
DSF-415S

Suction Filter
 DRY ALL