


## SealUp Removable AC/R Joint Sealant

- Creates a flexible but strong seal on the threaded or flanged AC/R fittings, adhering to internal surfaces and filling all micro-cracks.
- Prevents vibration from loosening nuts, joints, bolts, etc.
- Easy to remove.
- Can be applied on all plastics and metals.
- Temperature range use: -90°C to +200°C (-130°F to +392°F).
- Pressure range use: full vacuum and up to 500 bar/7250 psi.
- Resists refrigerant gases, combustible gases, refrigeration lubricants, fuels, solvents, industrial gases.
- Threaded spout for better sealing.

Art.-Nr.	Description	€				
TR1157.Y.01	50 mL tube	-	30	-	-	-



## Thor Sealant Remover and Surface Cleaner

- Removes sealant residues from surfaces. Ideal for cleaning surfaces before using External and FixQuick.
- Quick cleaning action: works in just a few minutes.

Art.-Nr.	Description	€				
TR1013.J.01	200 mL can	-	24	2880	3168	







200 mL



## Ezi Oil Thread Cutting Oil

- Necessary to lubricate copper pipes during flanging.
- Particularly suitable for lubricating drill bits, tap and die sets, reamers and other tools that cut or incise metal.

Art.-Nr.	€				
OL1009.J.01	-	24	2880	3168	



200 mL

